

THE UNRIVALED COOLER FOR THE AMD RYZEN™ THREADRIPPER™

ICe**SLEET**® X9 Dual TR




Dual Tower Cooler Featuring a 120 mm PWM Fan & 140 mm PWM Fan

- 9 Tuned Copper Heat Pipes
- Vivid ARGB Lighting
- Auto START and STOP Feature: The Fan is Silent, Until Duty Cycle Reaches 21% Loading
- Complete Bond Soldering Between Fin Sheets
- Copper Base Fully Covers the Chipset
- Nickel Plate Finishing









Specifications

280 W
46 mm
Ø 6 mm x 9
Aluminum Fins x 100, Thickness 0.4 mm, Copper Base
Nickel-plated
FUZEIce® Plus (0.8 g)
135 (L) x 150 (W) x 166 (H) mm
1,271 g
AMD sWRX8, sTRX4, sTR4, SP3
2-Year

Lighting

Туре	Addressable RGB
Connector	3-pin Addressable RGB Connector
Voltage / Current	5 V / 0.5 A

Fan

ize	120 mm x 1 / 140 mm x 1
peed	500 - 1850 RPM / 500 - 1600 RPM
irflow	76 CFM / 96 CFM
tatic Pressure	2.8 mm $H_2O / 2.65$ mm H_2O
Current	0.2 A / 0.23 A
′oltage	12 V
Bearing	Fluid Dynamic Bearing
loise Level	0 - 38 dBA (with Auto START/STOP)
Connector	4-pin PWM x 2
1TTF	> 150,000 hours

Box Content

